# For every industrial need

# Satsuma

## Versatile, full-featured and compact femtosecond laser

The Satsuma family of femtosecond lasers offers versatility in the most compact air-cooled laser platform on the market. Satsuma is a cost-efficient high repetition rate solution providing high energy, up to 150  $\mu J$  in the IR with optional green, UV and deep UV outputs.

Versatile and fully-featured, Satsuma femtosecond lasers can be equipped with:

- > FemtoTrig<sup>™</sup> high precision synchronization to provide high ablation quality and high throughput, in a cost effective and easy to use option
- > FemtoBurst™ to control the micro-pulse number, pattern, inter-pulse delay from 25 to 100 ns

The Satsuma product range is globally recognised as the best-seller due to its ease of integration and unsurpassed engraving quality.

Satsuma is part of Amplitude's femtosecond laser range with very short pulsewidths ensuring the lowest HAZ (heat-affected zone) and highest ablation efficiency for industrial applications, and making it the ideal pump source for science.





#### **Industry**:

- > Microelectronics
- > Micromachining
- > Flat Panel Display Repair

#### Medical:

- > Ophthalmology
- > Medical Device Manufacturing



- > Air-cooled up to 20 W
- > FemtoTrig™
- > No burst length limitation
- > FemtoBurst™
- > Optional green, UV and DUV outputs
- > Industrial design for 24/7 operation



#### Science:

- > Multiphoton Imaging
- > Optogenetics
- > Ultrafast Spectroscopy

Specifications	Satsuma	Satsuma HP	Satsuma HP <sup>2</sup>
Pulse Width (fs)	< 350		
Repetition Rate	From single shot to 40 MHz		
Max Power (W)	5	10	20
Max Energy (μJ)	10	20	40
Reference Repetition Rate	500 kHz		
Central Wavelength	1030 +/- 5 nm		
$M^2$		<1.2	
Beam diameter (mm)	2.3 +/-0	),5 mm	2,7 +/-0,5 mm
Astigmatism		<50%	
Waist assymetry	< 13%		
Ellipticity	< 13%		
Pointing Stab	<25 μrad/°C		
p to p Stability	<1,5%RMS		
Power Stability (8 hrs)	<1%RMS		

# **OPTIONS**

Harmonic Generation	Integrated, Mono-wavelen	gth, up to 4-wavelengths
	Output wavelength - 51	5 nm, 343 nm, 257 nm
Femtotrig <sup>™</sup> - real pulse on demand	High precision triggering	Jitter 25 ns
Femtoburst <sup>™</sup> - arbitrary burst shaping	Defined pattern on request	
Burst Mode - unlimited intra-burst pulses	No length limitation	up to 80 pulses at 500 kHz



### Dimensions

Laser Head	52 x 33 x 12 cm
Power Supply	4U 19" rackable

## Weight

all Models	23 kg

## Cooling

Satsuma, HP, HP <sup>2</sup>	Air-cooled***

\*\*\*Water-cooled version available on request



Niji

Mango





Compress

Synchrolock